

mullins wheels

PRODUCT BULLETIN

MINE SPEC



Mullins Wheels has upgraded their range of CSA Ranger White and Black steel wheels to “Mine Spec – Load Rating”. Mullins has also added 12 new part numbers to their CSA Ranger steel wheel range.

All CSA Ranger White & Black Steel Wheels are rated with a Max Wheel Load suitable for mine specified vehicle applications.

CSA RANGER WHITE & BLACK NEW RELEASE MINE SPEC - LOAD RATED						
SIZE	PCD	FINISH	OFFSET	CENTRE CAP *	MAX LOAD KG	PART NUMBER
15x7	5/114.3	White	10 pos	401-145	1180	360-570P10-54W
15x7	5/114.3	Black	10 pos	401-145	1180	360-570P10-54B
15x7	5/139.7	White	6 neg	401-160	1180	360-570N06-57W
15x7	5/139.7	Black	6 neg	401-160	1180	360-570N06-57B
15x7	5/139.7	White	10 pos	401-160	1180	360-570P10-57W
15x7	5/139.7	Black	10 pos	401-160	1180	360-570P10-57B
15x7	6/139.7	White	6 neg	401-164	1180	360-570N06-67W
15x7	6/139.7	Black	6 neg	401-164	1180	360-570N06-67B
15x7	6/139.7	White	10 pos	401-160	1180	360-570P10-67W
15x7	6/139.7	Black	10 pos	401-160	1180	360-570P10-67B
16x6	5/150	White	0 pos	401-158	1500	360-660P00-515W
16x6	5/150	Black	0 pos	401-158	1500	360-660P00-515B
16x6	6/139.7	White	0 pos	401-160	1500	360-660P00-67W
16x6	6/139.7	Black	0 pos	401-160	1500	360-660P00-67B

CSA
ALLOY WHEELS

RK
RoadKing

MINE SPEC

CSA RANGER WHITE & BLACK NEW RELEASE MINE SPEC - LOAD RATED						
SIZE	PCD	FINISH	OFFSET	CENTRE CAP *	MAX LOAD KG	PART NUMBER
16x7	5/150	Black	5 pos	401-158	1500	360-670P05-515B
16x7	6/139.7	White	20 neg	401-164	1500	360-670N20-67W
16x7	6/139.7	Black	20 neg	401-164	1500	360-670N20-67B
16x7	6/139.7	White	0 pos	401-160	1500	360-670P00-67W
16x7	6/139.7	Black	0 pos	401-160	1500	360-670P00-67B
16x7	6/139.7	White	13 pos	401-160	1500	360-670P13-67W
16x7	6/139.7	Black	13 pos	401-160	1500	360-670P13-67B
16x7	6/139.7	White	30 pos	401-160	1500	360-670P30-67W
16x7	6/139.7	Black	30 pos	401-160	1500	360-670P30-67B
16x8	5/150	White	14 neg	401-158	1500	360-680N14-515W
16x8	5/150	Black	14 neg	401-158	1500	360-680N14-515B
16x8	6/114.3	White	20 pos	No Cap	900	360-680P20-64W
16x8	6/114.3	Black	20 pos	No Cap	900	360-680P20-64B
16x8	6/139.7	White	28 neg	401-164	1500	360-680N28-67W
16x8	6/139.7	Black	28 neg	401-164	1500	360-680N28-67B
16x8	6/139.7	White	0 pos	401-164	1500	360-680P00-67W
16x8	6/139.7	Black	0 pos	401-164	1500	360-680P00-67B
16x8	6/139.7	White	25 pos	401-164	1500	360-680P25-67W
16x8	6/139.7	Black	25 pos	401-164	1500	360-680P25-67B
17x8	5/150	White	0 pos	401-158	1150	360-780P00-515W
17x8	5/150	Black	0 pos	401-158	1150	360-780P00-515B
17x8	5/150	White	40 pos	401-158	1150	360-780P40-515W
17x8	5/150	Black	40 pos	401-158	1150	360-780P40-515B
17x8	6/139.7	White	0 pos	401-164	1150	360-780P00-67W
17x8	6/139.7	Black	0 pos	401-164	1150	360-780P00-67B
17x8	6/139.7	White	25 pos	401-164	1150	360-780P25-67W
17x8	6/139.7	Black	25 pos	401-164	1150	360-780P25-67B
Caps	401-145 or 401-145W 401-160 or 401-164					

Note: Vehicle operators must legally ensure that maximum axle load capacities are not exceeded



To check out all more vehicle fitment applications, visit us online today at

www.csadirect.com.au

think big