

## PRODUCT BULLETIN

## **Product Group: 9.00 x 22.5 Demountable Rims Bulletin No: 49**

Mullins Wheels has 9.00 x 22.5 Steel Demountable Truck Rims available for various truck steer and some drive applications. These rims fitted with wider tyres, may enhance steer characteristics and may improve load carrying characteristics on certain prime mover applications.

	MULLINS WI	HEELS - 9.00	x 22.5 DEMO	Dι	JNTABLE I	RIM - TRUCK FITME	NT GUIDE
Make	Model	Demountable Rim	Offset	Ī	Make	Model	Demountable Ri
D.A.F.	Late	9.00 x 22.5	102 mm	1	M.A.N.	Early	9.00 x 22.5
						Late	9.00 x 22.5
Ford	Reverse Steer (Check Track)	9.00 x 22.5	73 mm				
	Aeromax LTS	9.00 x 22.5	102 mm		Mercedes	Late Models	9.00 x 22.5
	LMT Louisville	9.00 x 22.5	102 mm			2228 Model	9.00 x 22.5
	LNT Louisville	9.00 x 22.5	102 mm				
	Louisville Early	9.00 x 22.5	102 mm		Scania	Reverse Steer (Check Track)	9.00 x 22.5
	Louisville Late	9.00 x 22.5	102 mm			Early - Cab Over	9.00 x 22.5
	LTD 9000	9.00 x 22.5	102 mm			Late	9.00 x 22.5
						R144 530	9.00 x 22.5
Freightliner	Reverse Steer (Check Track)	9.00 x 22.5	73 mm			Long Nose T Series	9.00 x 22.5
	Argosy 8x4 aqnd 6x4	9.00 x 22.5	102 mm				
					Sterling	LT7500	9.00 x 22.5
International	Reverse Steer (Check Track)	9.00 x 22.5	73 mm			LT9500	9.00 x 22.5
	Early Models	9.00 x 22.5	102 mm			AT9500	9.00 x 22.5
	Atkinson	9.00 x 22.5	102 mm				
	Acco 2350F, 2350G	9.00 x 22.5	102 mm		Volvo	Early	9.00 x 22.5
	Transtar 3600, 4700	9.00 x 22.5	102 mm			FL, FM9, FM12	9.00 x 22.5
	Eurotech	9.00 x 22.5	102 mm			FH, NH	9.00 x 22.5
	Eurostar	9.00 x 22.5	102 mm			Late	9.00 x 22.5
	Powerstar	9.00 x 22.5	102 mm				
	Iveco	9.00 x 22.5	102 mm		Western Star	Reverse Steer (Check Track)	9.00 x 22.5
						Early	9.00 x 22.5
Kenworth	Reverse Steer (Check Track)	9.00 x 22.5	73 mm			FL, FM9, FM12 FH, NH Late  Reverse Steer (Check Track)	9.00 x 22.5
	All Models	9.00 x 22.5	102 mm			5864SE, 6964F, 7564S	9.00 x 22.5
	K Model - Steer	9.00 x 22.5	102 mm			Constellation	9.00 x 22.5
	W Model - Steer	9.00 x 22.5	102 mm			Late	9.00 x 22.5
	K Model - Steer & Drive	9.00 x 22.5	127mm				
Kenworth	W Model - Steer & Drive	9.00 x 22.5	127mm		White	Reverse Steer (Check Track)	9.00 x 22.5
						All Models	9.00 x 22.5
Mack	Reverse Steer (Check Track)	9.00 x 22.5	73 mm				
	Early	9.00 x 22.5	102 mm				
	Late	9.00 x 22.5	127mm				
	CHR CLR	9.00 X 22.5	102 mm				
	Magnum	9.00 X 22.5	102 mm				
	Metroliner	9.00 X 22.5	102 mm			9	
	Value Liner	9.00 X 22.5	102 mm			CONTRACTOR OF THE PARTY OF THE	
	Super Liner	9.00 X 22.5	102 mm				
	i .		1	1			Filmon

Make	Model	Demountable Rim	Offset	
M.A.N.	Early	9.00 x 22.5	102 mm	
	Late	9.00 x 22.5	102 mm	
Mercedes	Late Models	9.00 x 22.5	127 mm	
	2228 Model	9.00 x 22.5	127 mm	
Scania	Reverse Steer (Check Track)	9.00 x 22.5	73 mm	
	Early - Cab Over	9.00 x 22.5	102 mm	
	Late	9.00 x 22.5	102 mm	
	R144 530	9.00 x 22.5	102 mm	
	Long Nose T Series	9.00 x 22.5	127mm	
Sterling	LT7500	9.00 x 22.5	102 mm	
	LT9500	9.00 x 22.5	102 mm	
	AT9500	9.00 x 22.5	102 mm	
Volvo	Early	9.00 x 22.5	127 mm	
	FL, FM9, FM12	9.00 x 22.5	102 mm	
	FH, NH	9.00 x 22.5	102 mm	
	Late	9.00 x 22.5	127 mm	
Western Star	Reverse Steer (Check Track)	9.00 x 22.5	73 mm	
	Early	9.00 x 22.5	102 mm	
	4864FX, 4964EX, 4964FX,	9.00 x 22.5	102 mm	
	5864SE, 6964F, 7564S	9.00 x 22.5	102 mm	
	Constellation	9.00 x 22.5	102 mm	
	Late	9.00 x 22.5	102 mm	
White	Reverse Steer (Check Track)	9.00 x 22.5	73 mm	
	All Models	9.00 x 22.5	102 mm	

## Mullins Part Numbers: 9.00 x 22.5 Demountable Rims

9.00 X 22.5

9.00 X 22.5

Vision

Quantum

700-465 9.00 x 22.5 Demountable Rim 102 mm Offset 700-470 9.00 x 22.5 Demountable Rim 127 mm Offset 700-475 9.00 x 22.5 S.A. Reverse Steer 73 mm Offset

Note: Reverse steer rims are also available - made to order - in chrome plated finish



DISCLAIMER: Mullins Wheels Pty Ltd recommends that a check be made with the relevant state government transport authority for wheel and vehicle suitability in regards to vehicle track dimensions and wheel and tyre load rating compatibility to the vehicle prior to wheel purchase by the customer. Note: Please use this list as a guide only as individual trucks may vary. It is recommended to check all clearances (e.g. brake booster) prior to fitment

102 mm

102 mm



